
Decision Document

Solid Waste Management Unit B-23 Building 103-30 Production Area Hawthorne Army Depot Hawthorne, Nevada



October 2001





Decision Document SWMU B-23

NOV 2 1 2001

ENVIKURAMENTAL PROTECTION

October 2001

The selected remedy is protective of human health and the environment. It has been shown that a complete pathway to human health and the environment does not exist, and there is no potential for an exposure pathway to be completed in the future.

U.S. Army

1 9 NOV 2001

Anne L. Davis

Lieutenant Colonel, U.S. Army

Commanding

State of Nevada

30 Nov 2001

Paul Liebendorfer

Chief, Bureau of Federal Facilities

Decision Document

Solid Waste Management Unit B-23 Building 103-30 Production Area Hawthorne Army Depot Hawthorne, Nevada



October 2001





Decision Document SWMU B-23 Building 103-30 Production Area Hawthorne Army Depot Hawthorne, Nevada

1.0 Introduction

This decision document describes the rationale for the proposed closure of SWMU B-23, building 103-30 Production Area, at the Hawthorne Army Depot (HWAD), Hawthorne, Nevada. The US Army Corps of Engineers, Sacramento District, prepared this document with the help of HWAD for the Nevada Division of Environmental Protection (NDEP).

Tetra Tech, Inc. (Tt), was tasked by the US Army Corps of Engineers, Sacramento District (USACE), to perform remedial investigations and groundwater monitoring at the Hawthorne Army Depot (HWAD), Hawthorne, Nevada. These tasks were conducted from 1993 through 1997, primarily at solid waste management units (SWMUs) designated by the Army and the Nevada Division of Environmental Protection (NDEP). The NDEP is the lead regulatory agency for environmental issues at HWAD. The purpose of the sampling w as to determine the extent and degree of environmental impacts, if any, associated with activities performed at each SWMU. The primary goal of the investigation was to assess the environmental impacts and to report the findings, present conclusions, and recommend any remediation, if necessary.

With guidance from the NDEP, basewide proposed closure goals (PCGs) for soil were established as acceptable levels so that SWMU closure could be recommended and to assist in directing the investigative efforts toward those SWMUs where the target analytes were of greatest concern (Appendix A). These PCGs were used as action levels throughout this investigation and are used for comparison with the detected analytes in this report.

2.0 Site History

SWMU B-23 is in the HWAD's Building 103 Group (Figure 1-1) and is an inactive unlined catchment pit located 174 feet south of Building 103-30 (Figure 1-2). The catchment pit measures 65 feet long by 15 feet wide and is up to 4 feet deep. The catchment pit has been eroded and partially filled with windblown sand.

The USACE, HWAD and the NDEP agreed to define boundaries of each SWMU using annotated monuments and survey pins. As part of Ecology and Environment, Inc's., (E&E) 1997 field investigations, a survey monument was constructed and surveyed at SWMU B-23. A brass survey pin on the monument designates the monument number HWAAP-96-1996 and the SWMU number B-23. Three corner pins were set and surveyed to define the SWMU boundary, with the monument at the northwest corner. The locations of these corner markers and the SWMU boundary are shown on Figure 1-2. The survey data for this SWMU are presented in Appendix B.

3.0 Site Conditions

The catchment pit at SWMU B-23 reportedly was in operation from 1940 to the early 1960s and received moderate amounts of reactive hazardous wastewater containing TNT and cyclotrimethlyenetrinitramine (RDX) from water-cooled ordnance cutting saws. The munitions handled at building 103-30 also contained metal components, which could have become part of the waste stream.

During E&E's 1994 investigation and Tt's 1997 through 2001 groundwater monitoring, the depth to groundwater was measured at approximately 117 feet below ground surface (bgs) at groundwater monitoring wells IRPMW40 and IRPMW41.

Based on the past uses of the catchment pit at SWMU B-23, and on the observations made during the previous site inspections, the target analytes at this SWMU were known to be explosives and metals.

4.0 Investigations

Soils encountered during E&E's investigation of SWMU B-23 were composed mostly of silty sands with some fine gravel; finer sandy silts were encountered at shallow depths. In 1994, sampling activities proposed by E&E for the remedial investigation at SWMU B-23 included collecting and analyzing both surface and subsurface soil samples. One surface soil sample and one near-surface soil sample were collected from both sample locations HA01 and HA02 at SWMU B-23. The subsurface investigation at SWMU B-23 consisted of one cone penetrometer test (CPT) sounding with an adjacent sample boring, CPS01, drilled on the north side of the catchment pit, as shown on Figure 3-1. The sounding was advanced to a total depth of 111 feet bgs with no indication of groundwater. The CPT soil sample location was selected from the top 18 inches of a fine-grained horizon at a depth of 10 feet bgs based on the interpretation of the CPT sounding log.

5.0 Investigation Results

Arsenic (2.9 mg/kg to 4.3 mg/kg), barium (57 mg/kg to 86 mg/kg), total chromium (3.5 mg/kg to 6.7 mg/kg), and lead (3.0 mg/kg to 24 mg/kg) were detected in all the surface and near-surface soil samples collected at locations HA01 and HA02. Mercury was detected only in the surface soil sample collected from location HA01 at a concentration of 0.18 mg/kg. No other metals were detected in these surface and near-surface samples.

Arsenic at 2.3 mg/kg, barium at 130 mg/kg, total chromium at 6.7 mg/kg, and lead at 13 mg/kg were detected in the subsurface soil sample collected at location CPS01. No other metals were detected in this subsurface sample.

The laboratory results of all four surface and near-surface soil samples collected from this catchment pit detected TNT (0.54 mg/kg to 150,000 mg/kg), octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazocine (HMX) (0.93 mg/kg to 4,000 mg/kg), and RDX (4.3 mg/kg to 33,000 mg/kg). 1,3,5-trinitrobenzene (TNB) was detected in both the surface and five-foot sample collected from

HA01 and the five-foot sample collected from sample location HA02 at concentrations ranging from 1.4 mg/kg to 13 mg/kg. 2,4-Dinitrotoluene (DNT) and picric acid were detected only in the surface sample collected from sample location HA01 at concentrations of 12 mg/kg and 1.5 mg/kg, respectively. No explosives were detected in the subsurface soil sample collected from location CPS01. Appendix C has the analytical results of these investigations and figure 3-1 shows the locations of the samples.

At SWMU B-23, the detected metals arsenic, barium, total chromium, lead, and mercury, which are common in the Walker Lake Valley soils, are evaluated to be at naturally occurring concentrations near their background levels. All of these metals were reported at concentrations that did not exceed their PCGs.

The soil at SWMU B-23 has been impacted with explosives and requires a remediation action. The extent of the contamination was within the pit area and about 5 feet deep, based on the limited depths of soil contamination, it is not likely that groundwater has been impacted by explosives from this site.

6.0 Remediation

It was determined that this SWMU would be excavated and resampled. The excavated soil would be treated as part of the base-composting program.

7.0 Remediation Results

SWMU B-23 had 105 cubic yards of material excavated and placed in the composting windrow 5D. The analytical results from the sample and the samples from window 5D are shown in Appendix D, the location of the confirmation samples are shown in figure 4. The confirmation samples were less than HWAD PCGs for all compounds.

8.0 Public Involvement

It is the US Department of Defense and Army policy to involve the local community throughout the investigation process at an installation. To initiate this involvement, HWAD has established and maintains a repository library at the local public library. This repository includes final copies of all past studies and other documents regarding environmental issues at HWAD. As future environmental documents are made available to HWAD the repository shall be updated.

HWAD has solicited community participation in establishment of a restoration and advisory board (RAB). To date there has been insufficient response and HWAD has not formed a RAB. HWAD has held open houses to inform the public of on going environmental issues. HWAD shall continue to solicit community involvement, and will establish a RAB should sufficient community interest be obtained.


9.0 Conclusions

The contaminated soil has been removed from SWMU B-23 and has been treated in the composting windrows to levels below clean up goals. SWMU B-23 should be returned to the base site master plan with the restriction of no construction within the SWMU area.

10.0 REFERENCES

- Ecology and Environment. 1995. RCRA Facility Assessment Report for 24 Solid Waste Management Units, Hawthorne Army Depot, Hawthorne, Nevada. April 1995.
- Jacobs Engineering, 1988. RCRA Facility Assessment, Hawthorne Army Ammunition Plant, TES IV Work Assignment No. 433.
- Millsap, Herman. 1977. Hawthorne Army Depot. Personal communication via telephone with Richard Brunner of Tetra Tech, July 17, 1997.
- RAI. 1992. Site Screening Inspection (SSI) for the Hawthorne Army Ammunition Plant, Hawthorne, Nevada. Prepared for the US Army Corps of Engineers Toxic and Hazardous Materials Agency by Resource Applications, Inc., Falls Church, Virginia. December 1992.
- Tetra Tech. 1997a. Draft Quarterly Ground Water Monitoring Report, First Quarter 1997, Hawthorne Army Depot, Hawthorne, Nevada. April 1997.
- _____. 1997b. Quarterly Ground Water Monitoring Report, Second Quarter 1997, Hawthorne Army Depot, Hawthorne, Nevada. July 1997.
- . 1997c. Final Data Package with recommendations for future action, Group B solid waste management units, Hawthorne Army Depot, Hawthorne, Nevada, Volumes 1, 2a, and 2b. January 1997.
- _____. 1997d. Final Technical Memorandum Background Sampling at the Hawthorne Army Depot, Hawthorne, Nevada. March 1997.
- . 1998. Final Remedial Investigation Report, Hawthorne Army Depot, Hawthorne, Nevada. December 1998.
- USACE. 1995. Risk Assessment Handbook: Volume I Human Health Assessment (EM 200-1-4). USACE. June 1995.
- USAEHA. 1988. Final Report. Ground Water Contamination Survey No. 38-26-0850-88. Evaluation of Solid Waste Management Units. HWAAP, Hawthorne, Nevada. May 12-19, 1987 and August 1-5, 1988.

- USATHAMA. 1977. Installation Assessment of Naval Ammunition Depot, Hawthorne, Nevada. U.S. Army Toxic and Hazardous Materials Agency, Aberdeen Proving Ground, Maryland. Records Evaluation Report No. 114.
- USEPA. 1989. Risk Assessment Guidance for Superfund. Volume I Human Health Evaluation Manual (Part A). December 1989.
- _____. 1996. Region IX Preliminary Remediation Goals. USEPA Region IX. August 1996.
- WaterWork. 1990. Hawthorne Army Ammunition Plant, Area 101 Surface Impoundments, Field and Lab Data and Analysis, Attachment 1-8.





Site Location Map SWMU B23 Building 103-30 Catchment Pit


Hawthorne Army Depot Hawthorne, Nevada

Figure 1-1

Tetra Tech, Inc.







Appendix A

Proposed Closure Goals Hawthorne Army Depot Hawthorne, Nevada

	nawiiioiii	c, 1101444		
·	Chemical	Carcinogenic (C) or Non- carcinogenic	HIVAD Proposed Clasure Goals for Soil (mg/kg)	HWAD Proposed Glosure Goal Saurce
CONSTRUCTION CONTENT	Classification	NC I	128,000	Calculated Subpart S*
itrate	Anion	NC	•	NA°
-Amino-dinitrotoluene	Explosive	NC		NA .
-Amino-dinitrotoluene	Explosive	NC	· . 8	Calculated Subpart S
3-Dinitrobenzene	Explosive	NC	160	Calculated Subpart S
,4-Dinitrotoluene	Explosive	NC	80	Calculated Subpart S
,6-Dinitrotoluene	Explosive	NC	4,000	Calculated Subpart S
IMX	Explosive	NC	40	Calculated Subpart S
litrobenzene	Explosive	NC NC	800	Calculated Subpart S
litrotoluene (2-, 3-, 4-)	Explosive		64	Calculated Subpart S
ROX	Explosive	NC NC	800	Calculated Subpart S
etryl	Explosive	NC .	4	Calculated Subpart S
,3,5-Trinitrobenzene	Explosive	. "NC ·	233	Calculated Subpart S
2,4,6-Trinitratoluene	Explosive	C .	80,000	Calculated Subpart S
Atuminum	Metai	NC	30	Background ^e
Arsenic (cancer endpoint)	Metal	C & NC	_	Calculated Subpart S
Barium and compounds	Metal	NC	5,600	Background
Beryllium and compounds	Metal	С	40	Calculated Subpart S
Cadmium and compounds	Metal	NC	1	Calculated Subpart S
Chremium III and compounds	Metal	NC	80,000	PRG ¹
Lead	Metal	NC	1000	Calculated Subpart S
Mercury and compounds (inorganic)	Metal	ИС	24	Calculated Subpart S
Selenium	Metal	NC	400	Calculated Subpart S
Silver and compounds	Metal	NC	400	Calculated Subpart S
Acenaphthene	PAH	NC	4,800	Calculated Subpart S
Benzo(ajanthracene	PAH	C	0.96	Detection Limit
Benzo[a]pyrene	. PAH	C	0.10	Calculated Subpart 5
Benzo[b]fluoranthene	PAH	C	0.96	Calculated Subpart S
Benzo[k]fluoranthene	PAH	C	10	Calculated Subpart
Chrysene	PAH	С	. 96	Calculated Subpart
Dibenz[ah]anthracene	PAH	С	0.96	Calculated Subpart
Fluoranthene	PAH	NC	3,200	Calculated Subpart
Fluorene	PAH	NC	3,200	NA NA
Indeno[1,2,3-cd]pyrene-	PAH	С	-	Calculated Subpart
Naphthalene	PAH	NC	3,200	Calculated Subpart
Pyrene	PAH	NC	2,400	NOEP Level Clean-
Total Petroleum Hydrocarbons as Diesel (TPH-d)	PAH	С	100.	TSCA ⁹
Polychlorinated biphenyls (PCBs)	PCBs	С	<u> </u>	Calculated Subpart
Sis(2-ethylnexyl)phthalate (DEHP)	svoc	С	1,600	Calculated Support
Bromoform (tribromomethane)	svoc	C	89	0110311100 0 = 27

Proposed Closure Goals Hawthorne Army Depot Hawthorne, Nevada

	Ghemical	(C) or Non- carcinogenic	HAIAD Proposed Classe Gods for	HWAO Proposed
Constituent of Concern	\$45,750 \$27,979 c 900 pp and 200 \$200 \$	(NC)	Sall (marka)	Closure Goal Source Calculated Subpart S
utyl benzyl phthalate	svoc	ИС	16,000	Calculated Subpart S
ibromochloromethane	svoc	¢	83	·
ibutyl-phthalate	svoc	NC	8,000	Calculated Subpart S
liethyl phthalate	svoc	NC	64,000	Calculated Subpart S NA
henanthrene	svoc		-	Calculated Subpart S
Phenol	svoc	NC	48,000	Calculated Subpart S
cetona	VOC .	NC	800	Calculated Subpart S
Anthracene	voc	NC	24,000	Calculated Subpart S
Benzene	voc	C	24	
Bis(2-chloroisopropyl)ether	· voc	. c	3,200	Calculated Subpart S
Bromomethane	voc	. NC	112	Calculated Subpart S
Carbon tetrachloride	voc	c c	5	Calculated Subpart S
Chlorobenzene	voc	NC	1,600	Calculated Subpart S
Chloroform	voc	С	115	Calculated Subpart S
Chicromethane	voc	С	538	Calculated Subpart S
Dibromomethane	voc	С	0.008	Calculated Subpart S
1,2-Dichlorobenzene	voc	NC	7,200	Calculated Subpart S
1,4-Dichlorobenzene	voc	С	18,300	Calculated Subpart S
1,40ichiorocenzene Dichlorodifluoromethane	voc	С	16,000	Calculated Subpart S
	voc	NC	8,000	Calculated Subpart S
Ethylbenzene	l voc	NC	200	Calculated Subpart S
Methylene bromide	voc	С	4,800	Calculated Subpart S
Methylene chloride	voc		-	NA NA
2-Methylnaphthalene 1,1,2,2-Tetrachloroethane	voc	С	35	Calculated Subpart S
Tetrachioroethylene (PCE)	voc	C&NC	800	Calculated Subpart S
i	voc	NC	16,000	Calculated Subpart S
Toluene	vọc	NC	7,200	Calculated Subpart S
1,1,1-Trichloroethane	voc	C&NC	480	Calculated Subpart S
Trichloroethylene (TCE)	voc	NC	24,000	Calculated Subpart S
Trichlorofluoromethane	voc	С	480	Calculated Subpart S
1,2,3-Trichloropropane	voc	С	0.37	Calculated Subpart
Vinyl chloride	voc	NC	160,000	Calculated Subpart
Xylene Total (m ₇ , o-, p-) 2,3,7,8-TCDD	Dioxin	c	0.000005	Calculated Subpart

^{*} RCRA 55 FR 30870

Not available

^e Highest background concentration detected in 50 background soil samples

⁴ Smucker, Stanford J. USEPA Rgion IX, Preliminary Remedial Goals, Second Half, Sep. 1995

^{*} Mathod detection limit for Volatile Organic Compounds by EPA Method 8260 or

Semi-Volatile Organic Compounds analyzed by EPA Method 8270

^fNevada Division of Environmental Protection

⁹ Cleanup level for PCB spills in accordance with Toxic Substance and Control Act Spill Policy Guidelines 40 CFR 761


Clean-up Goals by Screening* and Definitive Analysis

Contaminant	Concentration (mg/kg)
2,4,6,-trinitrotoluene (TNT)	40*
2,4-dinitrotoluene (2,4-DNT)	2.6
2,6-dinitrotoluene (2,6-DNT)	2.6
1,3,5-trinitrobenzene (1,3,5-TNB)	4
1,3,-drinitrobenzne (1,3-DNB)	. 8
2-amino-4,6dinitrotoluene (2-Am-DNT)	NE
4-amino-2,6-dinitrotoluene (4-Am-DNT)	NE
Octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazocine (HMX)	100
Hexahydro-1,3,5-trinitro-1,3,5-triazine (RDX)	64
Pieric acid	7
Pentachlorophenol	None


Proposed Excavation Goal (PEG's) by Definitive and Screening * Analysis-Maximum Concentration of Contaminants In Soil to Be Left in Place at Depth Below the Surface


Contaminant	Concentration (mg/kg)
2,4,6,-trinitrotoluene (TNT)	800*
2,4-dinitrotoluene (2,4-DNT)	80
2,6-dinitrotoluene (2,6-DNT)	80
1,3,5-trinitrobenzene (1,3,5-TNB)	150
1,3,-drinitrobenzne (1,3-DNB)	NE
2-amino-4,6dinitrotoluene (2-Am-DNT)	NE
4-amino-2,6-dinitrotoluene (4-Am-DNT)	NE
Octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazocine (HMX)	4000
Hexahydro-1,3,5-trinitro-1,3,5-triazine (RDX)	300
Picric acid	7.0
Pentachlorophenol	NE
Nitroaromatics/Nitroamines	<30

Appendix B



NW COR 14508245.570 Ν 2613792.905 Ε ELEV 4161.405 NE COR 14508308.687 Ν 2613900.788 Ε ELEV 4160.979 SE COR 14508274.073 Ν Ε 2613920.807 SW COR ELEV 4161.705 N 14508210.829 2613812.902 ELEV 4161.842









COMSTOCK LAND SURVEYING

777 LA RUE AVENUE, SUITE A RENO, NEVADA 89509 PH. (702) 329-2072

SWMU B23 Survey Data Hawthorne Army Depot Hawthorne, Nevada

SWMU	Point ID	Northing (feet)	Easting (feet)	Elevation
B23	HA01	1384947.22	489479.19	4156.29
B23	HA02	1384922.31	489441.94	4156.43
B23	CPS01	1384936.44	489428.82	4160.33
B23	HWAAP-96-1996	1384920.34	489389.61	4161.41
B23	Pin 1	1384983.46	489497.49	4160.98
B23	Pin 2	1384948.85	489517.51	4161.71
B23	Pin 3	1384885.60	489409.61	4161.84

Notes:

NE = Not established

Coordinate data based on electronic map file using the NAD 1927 datum.

Elevation data based on surveyors map using NGVD 1929 datum.

Appendix C

Nitrogen Method 353.2 (ASC)

Sample ID	Location ID	Sample Date	Depth	Nitrogen Nitrate
			40	mg/kg
B23-CPS1-1-010	CPS01	5/18/94	10	<1.1
Analyses			•	1
Detections				0
Minimum Concentration				0
Maximum Concentration				0
HWAD - PCG				128000
HWAD - PCG Hits				0

Notes:

NE = Not established

Zero values listed for maximum and minimum concentrations indicate a nondetect value for that analyte.

<u>.</u>	<u>ë</u>	Sample	ebth	muhs	euyllium	muimbs	stoT muimond(Silver	oinsen/	peə	muinələ
ö	cation ID	Cale	ه ا	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg
	1004	3/20/01	0.5	7.2	9 <u>.</u>	<0.56	6.7	\	Š	Š	Š
	1A01	3/20/91	, rc	29	<0.52	<0.52	3.5	⊽	3.1	3.9	<0.52
	1A02	3/20/91	S C	57	<0.52	<0.52	3.5	٧	2.9	.w	<0.52
1.	1A02	4/27/94	0.5	98	<0.51	<0.51	5.1	⊽	4.3	5.8	<0.51
· <u>0</u>	CPS01	5/18/94	10	130	<0.53	<0.53	6.7	4.1	2.3	13	<0.53
				5	2	5	5	5	4	4	4
				ıc	0	0	വ	0	4	4	0
Detections Minimum Concentration				57	0	0	3.5	0	2.3	က	0
Maximum Concentration				130	0	0	6.7	0	4.3	13	0
				2000	-	20	20	100	100	100	20
				0	0	0	0	0	0	0	0

Notes: NA = Not analyzed Zero values listed for maximum and minimum concentrations indicate a nondetect value for that analyte.

Arsenic Method 7060 (ASC)

•				
Sample ID	Location ID	Sample Date	Depth	Arsenic
				mg/kg
B23-HA1-1-000	HA01	3/20/91	0.5	2.9
B23-HA1-1-005	HA01	3/20/91	5	3.1
B23-HA1-2-005	HA02	3/20/91	5	2.9
B23-HA1-2-000	HA02	4/27/94	0.5	4.3
B23-CPS1-1-010	CPS01	5/18/94	10	2.3
Analyses				5
Detections				5
Minimum Concentration				2.3
Maximum Concentration				4.3
HWAD - PCG				100
HWAD - PCG Hits			_	0

Lead Method 7421 (ASC)

Sample ID	Location ID	Sample Date	Depth	Lead
				mg/kg
B23-HA1-1-000	HA01	3/20/91	0.5	24
B23-HA1-1-005	HA01	3/20/91	5	3.9
B23-HA1-2-005	HA02	3/20/91	5	3
B23-HA1-2-000	HA02	4/27/94	0.5	5.8
	,		.,	
Analyses				4
Detections				4
Minimum Concentration				3
Maximum Concentration				24
HWAD - PCG				100
HWAD - PCG Hits				0

Mercury Method 7471 (ASC)

·				
Sample 1D	Location ID	Sample Date	Depth	Mercury
				mg/kg
DOC 1144 4 000	11001	3/20/91	0.5	0.18
B23-HA1-1-000	HA01	.		
B23-HA1-1-005	HA01	3/20/91	5	<0.1
B23-HA1-2-005	HA02	3/20/91	5	<0.1
B23-HA1-2-000	HA02	4/27/94	0.5	<0.1
B23-CPS1-1-010	CPS01	5/18/94	10	<0.11
Analyses				5
Detections				1
Minimum Concentration				0.18
Maximum Concentration				0.18
HWAD - PCG				24
HWAD - PCG Hits				0

Selenium Method 7740 (ASC)

Sample ID	Location ID	Sample Date	Depth	Selenium
				mg/kg
B23-HA1-1-000	HA01	3/20/91	0.5	<0.56
B23-HA1-1-005	HA01	3/20/91	5	<0.52
B23-HA1-2-005	HA02	3/20/91	5	<0.52
B23-HA1-2-000	HA02	4/27/94	0.5	<0.51
B23-CPS1-1-010	CPS01	5/18/94	10	<0.53
Analyses				. 5
Detections				0
Minimum Concentration				0
Maximum Concentration				0
HWAD - PCG				20
HWAD - PCG Hits				0

Note:

Zero values listed for maximum and minimum concentrations indicate a nondetect value for that analyte.

XMH eneznedonitrid-m	/kg mg/kg			- ,	16 <1					93 0			0	
XWH	mg/kg	4000	_	Ö.	•					Ö	4000	40		
4-Nitrotoluene	mg/kg	₹	⊽	⊽	⊽	⊽		5	0	0	0	OOR	0	-
TMG-8,S-onimA-₽	mg/kg	2	⊽	⊽	₹	₹		5	0	0	0	Ц	! !	
3-Nitrotoluene	mg/kg	۲	⊽	۲	⊽	⊽		5	0	0	0	OOB	80)
S-Nitrotoluene	mg/kg	۲	⊽	٧	⊽	۷		5	0	0	0	000	8	>
TVQ-8,4-onimA-S	mg/kg	₹	⊽	⊽	⊽	۲	-	5	0		0	Ľ	볼	1
eneulototiniG-8,S	mg/kg	⊽	⊽	⊽	⊽	⊽		5	C	0	0	Ċ	g c	>
ənəulotortiniQ-4,S	mg/kg	12	⊽	⊽	⊽	⊽		5	· 	. 5	12	Ċ	2.0 1	_
TNT-8,4,S	mg/kg	150000	780	; , ;	0.54	⊽		5.	4	0.54	150000	Ċ	233 2	7
Depth		0.5	വ	, rc	_									
Sample Date	i	3/20/91 0.5	3/20/91	3/20/91	4/27/94	5/18/94								
Sampl Location ID Date		HA01	HA01	HA02	HA02	CPS01								
Sample ID		B23-H41-1-000	523-1171-1-005 823-1471-1-005	B23-11A1-1-003 B23 HA1 2 OOE	B23-HA1-2-003 B23-HA1-2-000	B23-CPS1-1-010		A COLLON	Allalyses	Detections	Maximum Concentration		HWAD - PCG	

Explosives Method 8330 (ASC)

Notes: NE = Not established Zero values listed for maximum and minimum concentrations indicate a nondetect value for that analyte.

000	6 4. 4. 13	5 4 4.3 33000	000				Analyses Detections Minimum Concentration Maximum Concentration
⊽	V	⊽	⊽	2	5/18/94	CPS01	B23-CPS1-1-010
₹ ₹	₹ ₹	78	⊽ '	0.5	4/27/94	HA02	B23-HA1-2-000
⊽	1.4	4.3	₹	က	3/20/91	HA02	B23-HA1-2-005
₹	7.3	280	⊽	5	3/20/91	HA01	B23-HA1-1-005
₹	13	33000	₹	0.5	3/20/91	HA01	B23-HA1-1-000
mg/kg	mg/kg	mg/kg	mg/kg				
l(y)	sym-Trinitrobenzene	ХДЯ	Witrobenzene	Debth	Sample Date	Location ID	Sample ID

HWAD - PCG HWAD - PCG Hits

Notes:

NE = Not established

Zero values listed for maximum and minimum concentrations indic

800

4 0

64

0 0

Picric Acid Method 8330M (ASC)

				g
		Sample	Ē	Picric Acid
Sample ID	Location ID	Date	Depth	Pic
·				mg/kg
				mgmg
B23-HA1-1-000	HA01	3/20/91	0.5	1.5
B23-HA1-1-005	HA01	3/20/91	5	<0.25
B23-HA1-2-005	HA02	3/20/91	5	<0.25
B23-HA1-2-000	HA02	4/27/94	0.5	<0.25
B23-CPS1-1-010	CPS01	5/18/94	10	<0.25
A1				5
Analyses				1
Detections Minimum Concentration				1.5
				1.5
Maximum Concentration				1.5
HWAD - PCG				7
HWAD - PCG Hits				0

Notes:

NE = Not established.
HWAD Action Level based on guidance from ASTDR

and NDEP approval.

Nitrate/Nitrite Method 9200 (ASC)

Sample ID	Location ID	Sample Date	Depth	Nitrate-Nitrogen
				mg/kg
B23-HA1-1-000 B23-HA1-1-005 B23-HA1-2-005 B23-HA1-2-000	HA01 HA01 HA02 HA02	3/20/91 3/20/91 3/20/91 4/27/94	0.5 5 5 0.5	32 1.9 <1 5.4
Analyses Detections Minimum Concentration Maximum Concentration				4 3 1.9 32
HWAD - PCG HWAD - PCG Hits				128000 0

Appendix D

WINDROW CONFIRMATION SAMPLES

SWMU B-23

Tetra Tech Hawthorne Army Depot

ONSI7 ENVIRONMEN LABORATORIES,

Date Received: 6/6/00 Cooler ID: 0012 COC #: 002 Report No: 000606 SDG No: 000606exp Reported by: Chris Cao Matrix : soil Units : mg/Kg

Field Sample ID	No.	PAD01-WR 060100		PAD01-WR 060100		PAD01-WR 060100		PAD01-WR 060100		PAD01-WR		PAD01-WI 06010	
Lab Sample ID	No.	NAV01	6	NAV01	7	NAV01	В	NAV01	9	NAV02	0	NAV0	21 /
Sample Dept	h l	0		0		0		0		\ 0		0	/
Date Sample	d	6/1/00		6/1/00		6/1/00		6/1/00		6/1/00		6/1/00	/
Time Sample	đ	12:40		12:44		12:48		12:52		13:\\5		13:28	/
Date Extracte	xđ.	6/6/00		6/6/00		6/6/00	:	6/6/00		6/6/000		6/6/00	
Time Extracte	ed	16:40		16:40		16:40		16:40		16:40		16:40	
Date Analyze	xd xd	6/6/00	,	6/6/00		6/6/00	,	6/6/00)	6/6/00		6/17/0	0
Time Analyze	ed	22:39		22:58		23:17		23:36		23:55		0;/15	
Analytes	PQL	Conc.	Qual.	Conc.	Quai.	Conc.	Qual.	Conc.	Qual.	Conc.	∖Qual.	Gonc.	Qual.
HMX	4.4	18		12	ļ \$	16		35	! !	140	!\	/290	E
RDX	2.0	3.5		2.4	Ţ	4.5	!	15	! ! ;	10	$\lfloor \cdot \rfloor$	22	
1,3,5-TNB	2.0	3.1	U	2.8	U	3	U	2.8	ប	3.2	[U	/ 3.2	U
1,3-DNB	0.8	1.2	U	1.1	ļυ	1.2	U	1.1	U	1.3	U)	1.3	U
NB	1.6	2.5	U	2.2	υ	2.4	U	2.3	U	2.5	¦ ७/	2.6	U
Tetryl	8.4	13	υ	12	U	13	υ	12	U	13	. /	14	U
Amino-DNTs	2.4	3.7	U	3.4	υ	3.6	U	1.6	J	1.1	1/1	1.6]]
2,4.6-TNT	3.6	2	1 3	5.1	U	5.4	U	2.2	1	0.51	1 1	2.1	1
2,6-DNT	2.0	3.1	U	2.8	U	3	U	2.8	U	3.2	U	3.2	i u
2,4-DNT	1.6	2.5	υ	2.2	U	2.4	υ	2.3	U	2.5	U	2.6	U
2-NT	4.4	6.8	U	6.2	U	1.7	J	3.3	N	7 /	U	-7.1	U
4-NT	14.0	22	U	20	U	21	U	20	υ	22/	U	23	U
3-NT	6.8	11	υ	9.6	U	10	υ	9.6	υ	y/i	U	11	U V
Surrogate	QC Limits		1		i		į		T	/	i		i\
1,2-DNB	65%-135	0%		85%	<u> </u>	77%	!	55 %	į.	/53%	!	80%	-!\
Dilution Fact	or .	1		1:		-1		1] i		1	7
Percent Solid	s	68%		75%		71%		74%		67%		64%	

Notes:

U - Not detected at reported value

J- Between MDL and PQL

D - Dilution was performed on sample

E - Estimated value, result outside calibration range

DL - Surrogate diluted out due to high concentration of target compounds

PQL - Practical Quantitation Limit

N- non-confirmed by all three wavelengths

mg/Kg - Milligrams per kilogram (PPM)

SWMU CONFIRMATION SAMPLES

SWMU B-23

Applied P & Ch Laboratory
13760 Magnelia Ave. Chino CA 91710
Tel: (909) 590-1428 Fax: (909) 590-1408

APCL Analytical Report

_				Analysis Re	sult
Component Analyzed	Method	Unit	PQL	43 MB008D-C008-CC001-P	SMB23-GF001-F
				99-05898-9	99-05898-11
NITROAROMATICS AND NITROAMI	NES				
Dilution Factor				10 /	10
4-AMINO-2,6-DINITROTOLUENE	8330	mg/kg	0.2	ð.1 /	< 2.1
2-AMINO-4,6-DINITROTOLUENE	8330	mg/kg	0.2	-2J /	< 2.1
1,3-DINITROBENZENE	8330	mg/kg	0.25	<8.4	< 2.6
2,4-DINITROTOLUENE	8330	mg/kg	0.25	<3.4	< 2.6
2,6-DINITROTOLUENE	8330	mg/kg	0.25	<3.4	< 2.6
НМХ	8330	mg/kg	0.25	42	86
NITROBENZENE	8330	mg/kg	0.25	<3.4	₹2.6
3-NITROTOLUENE	8330	mg/kg	0.25	<3.4	< 2.6
RDX	8330	mg/kg	0.25	246 /	52
TETRYL	8330	mg/kg	0.25	<3.4	< 2.6
1,3,5-TRINITROBENZENE	8330	mg/kg	0.28	4.6∕	3J
2,4,6-TRINITROTOLUENE	8330	mg/kg	0.25	3 . /	105
2-NITROTOLUENE (4)	8330	mg/kg	0.25	< \$.4	< 2.6
4-NITROTOLUENE (4)	8330	mg/kg	6,25	4 3.4	< 2.6

				Analysis Result		
Component Analyzed	Method	Unit	PQL	SMB33-G5001-P 99-05898-12	SMB23-G5002-P 99-05898-13	
MOISTURE	ASTM-D2216	%Moisture	0.5	1.8	1.8	
NITROAROMATICS AND NITROAM!	NES					
Dilution Factor				1	1	
4-AMINO-2,6-DINITROTOLUENE	8330	mg/kg	0.2	< 0.20	< 0.20	
2-AMINO-4,6-DINITROTOLUENE	8330	mg/kg	0.2	< 0.20	0.13	
1,3-DINITROBENZENE	8330	mg/kg	0.25	< 0.25	< 0.25	
2,4-DINITROTOLUENE	8330	mg/kg	0.25	< 0.2ŏ	< 0.25	
2,6-DINITROTOLUENE	8330	mg/kg	0.25	< 0.25	< 0.25	
HMX	8330	mg/kg	0.25	9.18	1.5	
NITROBENZENE	8330	mg/kg	0.25	< 0.25	< 0.25	
3-NITROTOLUENE	8330	mg/kg	0.25	< 0.25	< 0.25	
RDX	8330	mg/kg	0.25	1.5	6.90	
TETRYL	8330	mg/kg	0.25	< 0.25	< 0.25	
1,3,5-TRINITROBENZENE	8330	mg/kg	0.25	< 0.25	0.2J	
2,4,6-TRINITROTOLUENE	8330	mg/kg	0.25	0.26	0.43	
2-NITROTOLUENE (4)	8330	mg/kg	0.25	< 0.25	< 0.25	
4-NITROTOLUENE (a)	8330	mg/kg	0.25	< 0.25	< 0.25	

				Analys	is Result
Component Analyzed	Method	Unit	PQL	SMB23-GS003-P 99-05898-14	SMB23-GS004-P 99-05898-15
MOISTURE	ASTM-D2216	%Maisture	0.5	0.9	1.6

Applied P & Ch Laboratory

13760 Magnolia Avc. Chino CA 91710 Tel: (909) 590-1828 Fax: (909) 580-1498

APCL Analytical Report

	Method Unit		_	LanA	ysis Result
Component Analyzed	Metho	d Unit	PQL	SMB23-GS003-P 99-05898-14	
NITROAROMATICS AND NITROAMI	NES			1	10
Dilution Factor	0000	D	0.3	< 0.20	< 2.0
4-AMINO-2,6-DINITROTOLUENE	8330			<0.20	< 2.0
2-AMINO-4,6-DINITROTOLUENE	8330			< 0.25	< 2,5
1,3-DINITROBENZENE	8330 8330			< 0.25	< 2.5
2,4-DINITROTOLUENE	8330			< 0.25	< 2.5
2,6-DINITROTOLUENE	8330 8330			0.98	12
HMX		· · · · · ·		< 0.25	< 2.5
NITROBENZENE	8330			< 0.25	< 2.5
3-NITROTOLUENE	8330 8330			5.10	62
RDX	8330		,	€ 0.25	c 2.5
TETRYL		— , —	•	0.1J	< 2.5
1,3,5-TRINITROBENZENE	8330 8330		•	8.53	12
2,4,6-TRINITROTOLUENE				< 0.25	< 2.5
2-NITROTOLUENE (a)	8330	_, -			< 2.5
4-NITROTOLUENE (a)	833() mg/kg	0.25	< 0.28	
					Analysis Result
Component Analyzed		Method	Unit	PQL	SMB23-G5005-P 99-05898-16
MOISTURE	A	STM-D2216	%Moist	11e 0.5	1.8
NITROAROMATICS AND NITROA	MINES				_
Dilution Factor					1
4-AMINO-2,6-DINITROTOLUEN	E	8330	mg/kg		< 0.20
2-AMINO-4,6-DINITROTOLUEN	E	8330	mg/kg		0.2J
1,3-DINITROBENZENE		8330	mg/kg	0.25	< 0.25
2,4-DINITROTOLUENE		8330	mg/kg	, 0.2 5	< 0.25
2,6-DINITROTOLUENE		8330	mg/ke		< 0.25
нмх		8330	mg/k		1.6
NITROBENZENE		8330	mg/ka		< 0.25
3-NITROTOLUENE		8330	mg/kį		< 0.25
RDX		8330	mg/kj	0.25	7.92
TETRYL		8330	mg/k	g 0.25	< 0.25
1,3,5-TRINITROBENZENE		833 0	mg/k		0.2J
2,4,6-TRINITROTOLUENE		8330	mg/k	g 0.25	0.74
2-NITROTOLUENE (a)		8330	mg/k		< 0.25
4-NITROTOLUENE (a)		8330	mg/k	g 0.25	< 0.25
				Analysis R	esult
Component Analyzed Method	Unit	PQL A	99-0589		3-WR002D-C002-CC001-P 99-05898-2
			1		1
Dilution Factor					

Appendix E




SWMU B-23: Facing southwest. Dredge pile on southwestern end of impoundment. R5N11. 9/29/94.



SWMU B-23: Facing northwest toward impoundment. Buildings 103-29 and 103-30 in the background. R5N14. 9/29/94.

September 1994



February 2000